



## Duramax Replacement Wear Parts for your Diamond Z 1463

---

### Tips/Teeth

- A Tip: 3"•x•5"•(7/8" Holes) Bottom Measurements
- AD Tip: 3"•x•5"•(7/8" Holes) Bottom Measurements
- ADT Tip: 3-3/8"•x•5-1/8"•(7/8" Holes) Bottom Measurements

### Hardware- Bolts, Nuts, Washers

#### Bolts

- 7/8" GWP Heavy Duty 2•1/2" – 7•1/2"•Fine
- 7/8" GWP Heavy Duty 2•1/2" – 7•1/2"•Coarse
- 7/8"•Regular•Headed•2•1/2" – 7•1/2"•Fine
- 7/8"•Regular•Headed•2•1/2" – 7•1/2"•Coarse

#### Nuts

- 7/8"•Flange•Nut•Lock Fine
- 7/8"•Flange•Nut•Lock•Coarse
- 7/8"•Flange•Nut•Fine
- 7/8"•Flange•Nut•Coarse
- 7/8"•Nut•Lock•Fine
- 7/8"•Nut•Lock•Coarse
- 7/8"•Non-Lock Nut Fine
- 7/8"•Non-Lock Nut Coarse

### Screens/Grates

- 1463 Screen 1- 1/4" Thick
- 1463•Screen•1" Thick
- Material: T-1, AR-400
- Hole Patterns (In Any Size)
  - Round
  - Diamond
  - Square
  - Octagon
  - Hexagon
  - Rectangle

- Herringbone
- Slanted
- Custom
- Options: Rails, Baffles, Hardfacing, Backing, Bevels, Anvils

## **Hammers-Fixed and Swing**

- 1463 Hammer•3" Thick Reversing
- 1463 Hammer•3" Thick Non-Reversing

## **Rods**

- 1463 Mill Rod Drilled and Tapped

## **Hammermills**

### **Cutter bars**

- 1463 Cutting Bar•2" Thick

### **Wear plates**

- 1463 Wear Plate

### **Deflector shields**

- 1463•Deflector•shield• $\frac{3}{4}$ " Thick T-1 With Replaceable Bolt On Wear Bar, Hardfaced or Carbided
- 1463 B Deflector Shield Replaceable Bolt On Wear Bar, Hardfaced or Carbided

### **Tub Rollers**

- 1463 Carrier Roller Double Bearing
- 1463 Side Roller Double Bearing
- 1463 Carrier Roller Single Bearing

### **Tub Chain**

- 1463•Tub•Teeth•1" Thick

## **Conveyor Belts**

- 1463 A Stage 1 Conveyor Belt
- 1463 A Stage 2 Conveyor Belt
- 1463 B Phase 1 Conveyor Belt
- 1463 B Phase 2 Conveyor Belt

## **Conveyor Drive and Idler Rollers**

- 1463 Idler Roller Phase 1
- 1463 Idler Roller Phase 2
- 1463 Drive Roller Phase 1
- 1463 Drive Roller Phase 2
- 1463 Magnetic Head Pulley

## **Misc.**

- 1463 Screen Rail Guide