



## Duramax Replacement Wear Parts for your Diamond Z 4000

---

### Tips/Teeth

- DS Tip: 2-1/2"•x•5"•(7/8" Holes) Bottom Measurements

### Hardware- Bolts, Nuts, Washers

#### Bolts

- 7/8" GWP Heavy Duty 2•1/2" – 7•1/2"•Fine
- 7/8" GWP Heavy Duty 2•1/2" – 7•1/2"•Coarse
- 7/8"•Regular•Headed•2•1/2" – 7•1/2"•Fine
- 7/8"•Regular•Headed 2•1/2" – 7•1/2"•Coarse

#### Nuts

- 7/8"•Flange•Nut•Lock•Fine
- 7/8"•Flange•Nut•Lock•Coarse
- 7/8"•Flange•Nut•Fine
- 7/8"•Flange•Nut•Coarse
- 7/8"•Nut•Lock•Fine
- 7/8"•Nut•Lock•Coarse
- 7/8"•Non-Lock Nut Fine
- 7/8"•Non-Lock Nut Coarse

### Screens/Grates

- 4000 Screen•1" Thick
- Material: T-1, AR-400
- Hole Patterns (In Any Size)
  - Round
  - Diamond
  - Square
  - Octagon
  - Hexagon
  - Rectangle
  - Herringbone
  - Slanted
  - Custom
- Options: Rails, Baffles, Hardfacing, Backing, Bevels, Anvils

## **Hammers-Fixed and Swing**

### **Rods**

- 4000 Mill Rod Drilled and Tapped

### **Hammermills**

### **Cutter bars**

### **Wear plates**

### **Infeed Chain**

- 4000 Complete Floor Chain

### **Conveyor Belts**

### **Conveyor Drive and Idler Rollers**