



Duramax Replacement Wear Parts for your Diamond Z E4800

Tips/Teeth

- A Tip: 3"•x•5"•(7/8" Holes) Bottom Measurements
- AD Tip: 3"•x•5"•(7/8" Holes) Bottom Measurements
- ADT Tip: 3-3/8"•x•5-1/8"•(7/8" Holes) Bottom Measurements
- C Tip: 2-1/2 X 2-1/2 (7/8" Hole) Bottom Measurements
- D Tip: 3"•x•5-1/4"•(7/8" Holes) Bottom Measurements

Hardware- Bolts, Nuts, Washers

Bolts

- 7/8" GWP Heavy Duty 2 1/2" – 7•1/2"•Fine
- 7/8" GWP Heavy Duty 2•1/2" – 7•1/2"•Coarse
- 7/8"•Regular•Headed•2•1/2" – 7•1/2"•Fine
- 7/8"•Regular•Headed•2•1/2" – 7•1/2"•Coarse

Nuts

- 7/8"•Flange•Nut•Lock•Fine
- 7/8"•Flange•Nut•Lock•Coarse
- 7/8"•Flange•Nut•Fine
- 7/8"•Flange•Nut•Coarse
- 7/8"•Nut Lock Fine
- 7/8"•Nut•Lock•Coarse
- 7/8"•Non-Lock Nut Fine
- 7/8"•Non-Lock Nut Coarse

Screens/Grates

- E4800•Screen•1" Thick
- Material: T-1, AR-400
- Hole Patterns (In Any Size)
 - Round
 - Diamond
 - Square
 - Octagon
 - Hexagon
 - Rectangle

- Herringbone
- Slanted
- Custom
- Options: Rails, Baffles, Hardfacing, Backing, Bevels, Anvils

Hammers-Fixed and Swing

Rods

- E4800 Mill Rod Drilled and Tapped

Hammermills

Cutter bars

Wear plates

Conveyor Belts

Conveyor Drive and Idler Rollers